

**FLUORO RUBBER COMPOSITION**

**Patent number:** JP1306454  
**Publication date:** 1989-12-11  
**Inventor:** SONOI TAKEHIRO; others: 01  
**Applicant:** NIPPON MEKTRON LTD  
**Classification:**  
**- international:** C08L27/12; C08K3/22; C08K5/34  
**- european:**  
**Application number:** JP19880135421 19880603  
**Priority number(s):**

**Also published as:**

 DE3915318 (A)

[Report a data error here](#)

**Abstract of JP1306454**

**PURPOSE:** To obtain a fluoro rubber composition having improved hygroscopicity, handling properties, stability, etc., as well as excellent curing physical properties, shaping properties, etc., by blending a fluoro rubber with a specific quaternary ammonium salt compound used as a curing accelerator.

**CONSTITUTION:** (A) 100 pts. wt. fluoro rubber is blended with (B) 1-40 pts. wt., preferably 3-15 pts. wt. oxide and/or hydroxide of bivalent metal (e.g., magnesium or calcium), (C) 0.5-10 pts. wt. preferably 0.5-1 pts. wt. polyhydroxy aromatic compound (e.g., bisphenol A) and (D) 0.1-5 pts. wt., preferably 0.1-2 pts. wt. quaternary salt compound expressed by the formula (R is 1-24C alkyl or 7-20C aralkyl; X<-> is tetrafluoroborate, etc.).

---

Data supplied from the **esp@cenet** database - Patent Abstracts of Japan